



BMDs

MEO-6000m

Smart Cart Mobile Workstation

A convenient mobile platform for your data processing equipment, the lightweight MEO-6000m is our newest addition to our cart product line. Constructed of lightweight materials, gliding on large polyurethane wheels, the smart design of the MEO-6000m, makes it a welcome addition to any research lab.

The top work surface trays overlap the frame and easily reposition left to right for user convenience and personal preferences. Dual mounting posts extend vertically above the top work surface and provide ergonomically desirable locations for securing flat screen displays, keyboard, hand-held scanners and other RFID reader system components. A second shelf offers space for an electronic balance or similar devices and a storage compartment, below the second shelf, houses other electronics such as the optional CPU's and additional equipment.

The MEO-6000m offers easy cleaning of the removable stainless steel trays. The T-slot frame construction allows for optional accessory mounting, providing unlimited custom configurations, strength and durability for years of reliable service.



Features & Benefits

- Mounting posts place keyboard, screen, ID-scanner, and other RFID reader system components at proper height.
- Top trays rest on frame, and are easily removable and interchangeable
- Top surface trays slide easily; weighing balance can be positioned in any corner
- Four swivel casters (two with locks) and polyurethane wheels for easy rolling
- Two 5-outlet power strips are installed in cabinet (International models are available upon request)
- Boom with counter-balance, for BMDs Smart Probes

www.BMDs.com



MEO-6000m Functional Overview



Physical Characteristics

Weight: 115 lbs.
 Length: 35.5 inches
 Height: 63 inches*
 Width: 24.5 inches

*increases to 81 inches with boom attachment

Construction

6105-T5 High Tensile Strength Aluminum frame
 Stainless Steel Shelving
 High Pressure laminate Trespa™ Panels

Wheels

5 inches in diameter x 2 inches wide polyurethane casters

50 foot long AC cord and two 5-outlet power strips are installed in the cabinet (international models are available upon request)

Hardware

**Keyboards, Monitors, Scales, Bar Code Scanners, and RFID Readers and system components are featured for illustration purposes only

Warranty

90 Days parts & labor

Design and specifications are subject to change without notice. Please visit us on the web at www.BMDS.com for the latest information, specifications, demonstrations, training and more!




Related Products


DAS-6009



IMI-1000



IPT-300



IPTT-300



Enlarged to show details

SP-6004/5



World Headquarters

Bio Medic Data Systems, Inc.
 1 Silas Road
 Seaford, Delaware 19973 U.S.A.
 Telephone: (302) 628-4100
 Toll Free: (800) 526-2637
 FAX: (302) 628-4110
www.BMDS.com

Visit us online at www.BMDS.com for the latest information, specifications, demonstrations, training and more!



Positive Animal Identification

© Copyright Bio Medic Corporation 2008, BMDS, Implantable Programmable Temperature Transponder, and the BMDS logo are trademarks of Bio Medic Data Systems, Inc. Covered by various U.S. and International patents and patents pending. U.S. Patent Nos. 5,481,262; 5,422,636; 5,074,318; 5,024,727; 5,252,962; 5,274,030; 5,420,579; 5,250,944; 5,262,772; DES. 351,151; DES. 330,891; 5,650,778; 5,002,548; 4,787,384; DES. 358,644. Design and specifications are subject to change without notice.